IN THE CLAIMS:

1. (Currently Amended) A spindle motor for use in a disc drive comprising a shaft supporting a thrust plate at one end thereof,

a sleeve surrounding the shaft and adjacent the thrust plate, the sleeve and cooperating with the shaft to define a journal bearing therebetween and cooperating with the thrust plate to define a fluid thrust bearing therebetween,

a counterplate welded to said sleeve and located adjacent said thrust plate, the counterplate and the thrust plate being adapted to retain a fluid therebetween,

the welded counterplate being adapted to contain fluid within the thrust bearing and the journal bearing.

- 2. (Original) A spindle motor as claimed in claim 1 wherein the shaft is fixed and the sleeve and counterplate rotate relative to the shaft.
- 3. (Original) A spindle motor as claimed in claim 2 wherein the sleeve supports a hub for supporting a disc for rotation about the shaft.
- 4. (Original) A spindle motor as claimed in claim 1 wherein the shaft is free to rotate relative to the sleeve and counterplate.
- 5. (Original) A spindle motor as claimed in claim 4 wherein the sleeve and counterplate are fixed to a base which supports the motor.
- 6. (Original) A spindle motor as claimed in claim 5 wherein the shaft supports a hub for rotation over said base.
- 7. (Original) A spindle motor as claimed in claim 6 wherein the hub supports one or more discs for rotation.
- 8. (Currently Amended) A spindle motor for use in a disc drive comprising a shaft supporting a thrust plate at one end thereof,
- a sleeve surrounding the shaft and adjacent the thrust plate, the sleeve and cooperating with the shaft to define a journal bearing therebetween and cooperating

with the thrust plate to define a fluid thrust bearing therebetween,

a counterplate supported between upraised axial arms of said sleeve and located adjacent said thrust plate, the counterplate and the thrust plate being adapted to retain a fluid therebetween.

means for containing fluid within the thrust bearing.

- 9. (Previously Presented) A spindle motor as claimed in claim 1 wherein said counterplate and said thrust plate define the fluid dynamic thrust bearing and the means for containing fluid comprise a counterplate welded to the upraised arms.
- 10, (Canceled)
- 11. (Currently Amended) A spindle motor for use in a disc drive comprising
 - a shaft
- a sleeve surrounding the shaft cooperating with the shaft to define a journal bearing therebetween
- a counterplate welded to upraised axial arms of said sleeve and located adjacent said thrust plate to define a fluid dynamic thrust bearing therebetween,

the welded counterplate adapted to contain fluid within the thrust bearing.

- 12. (Previously Presented) A spindle motor as claimed in claim 11 wherein the shaft is fixed and the sleeve and counterplate rotate relative to the shaft.
- 13. (Previously Presented) A spindle motor as claimed in claim 12 wherein the sleeve supports a hub for supporting a disc for rotation about the shaft.
- 14. (Previously Presented) A spindle motor as claimed in claim 11 wherein the shaft is free to rotate relative to the sleeve and counterplate.
- 15. (Previously Presented) A spindle motor as claimed in claim 14 wherein the sleeve and counterplate are fixed to a base which supports the motor.

- 16. (Previously Presented) A spindle motor as claimed in claim 15 wherein the shaft supports a hub for rotation over said base.
- 17. (Previously Presented) A spindle motor as claimed in claim 16 wherein the hub supports one or more discs for rotation.